DSS //









INAP-Profiler

safety helmet according to EN 397

Application field · construction zones

· industrial firms

· cold zones of construction and industry

· where the use of safety helmets is required

Shell · manufactured from Polyethylene (PE)

· innovative form with shell slightly drawn down at the neck

· lateral slots for ear defenders (30 mm)

· adjustable holes for effective ventilation

· 4- or 6-point webbed harness with chin strap fastenings Harness

· angled neckband

· exchangeable highly absorbent sweatband

· mounted foam cushion band

Additional testing · temperatures down to -20° C

Durability · up to 5 years

Size adjustment \cdot I - III / from 51 - 64 cm in steps of 0,5 cm

Weight of shell · approx. 250 g

Packing details · up to 30 helmets per model or colour in one box

Individualization · application of logos by silk screen method or self-adhesive foil,

reflective stripes, material dyeing in special colour or

fluorescent colour

Size of logos · front: approx. 60 x 40 mm / side: approx. 80 x 20 mm

Accessories/Spare parts · face protection, ear defenders, VOSS-Lock ratchet, chin straps

Sulfur yellow / RAL1016 Colours Signal white / RAL9003 4-Pnt-web. Harn. 11051016 6-Pnt-web. Harn. 11101016 4-Pnt-web. Harn. 11059003 6-Pnt-web. Harn. 11109003 Part No. Mint green / RAL6029 4-Pnt-web. Harn. 11052009 6-Pnt-web. Harn. 11102009 4-Pnt-web. Harn. 11056029 6-Pnt-web. Harn. 11106029 Signal blue / RAL5005 Carmine red / RAL3002 4-Pnt-web. Harn. 11053002 6-Pnt-web. Harn. 11103002 4-Pnt-web. Harn. 11055005 6-Pnt-web. Harn. 11105005

If you have any questions regarding our safety helmets or accessories please do not hesitate to get in contact with us at any time. VOSS-HELME GmbH & Co. KG, Kokenhorststraße 24, 30938 Burgwedel/Germany Tel.: +49 (0)5139 - 95 95 30 Fax: +49 (0)5139 - 95 95 39 Email: info@VOSS-HELME.de

